

Artist T4.8V Artist T8.8V

Multi Channel Class D Amplifier



With low impedance output and 70/100V outputs



Artist T4.8V and Artist T8.8V are with switch mode power supply and Class D circuit design, with high working efficiency, light weight and good reliability.

Artist T4.8V and Artist T8.8V multi channel Class D amps are with low impedance output and 70/100V output. For low impedance output, output power is 400W@8ohm each channel. Each channel can work at 4ohm. For 70/100V output, it's 100V/1000W or 70V/ 800W.

Artist T4.8V and Artist T8.8V are with modular design. Every two channels share one separate power supply and amplifier system.

With elaborately selected components and state-of-the-art craftwork, Artist T4.8V and Artist T8.8V have very good fidelity and high damping factor. It's good choice for music reproduction, speech and AV system integration.

Artist T4.8V

4-Channel Class D Amp



Artist T8.8V

8-Channel Class D Amp



		Artist T4.8V	Artist T8.8V
Rated Power (20Hz-20kHz, <0.1%THD)	8Ω Mono	4x400W	8x400W
	4Ω Mono	4x800W	8x800W
	70V	2x800W	4x800W
	100V	2x1000W	4x1000W
Working mode		Mono, parallel, 70V/100V	
Frequency Response (1W 8Ω stereo)		20Hz-20kHz(±0.5dB)	
Sensitivity		32dB	
Input /Output Connectors		Euroblock	
Input Impedance		Balanced >10kΩ / Unbalanced >10kΩ	
Crosstalk (20Hz-20kHz, Rated power 8Ω)		≥60dB	
S/N Ratio (Rated power 8Ω, A weighted)		≥108dB	
Damping Factor (1kHz&8Ω)		≥500	
Intermodulation Distortion (20Hz-20kHz, half power)		≤0.05%	
Total Harmonic Distortion (20Hz-20kHz, half power)		≤0.05%	
Slew Rate		≥45V/μs	
Output circuitry		Class D	
Power consumption	Idle	39W	78W
	1/8 output power	350W	720W
Rack Space		2U	
Dimensions (W×H×D)		483×88×450mm	
Net Weight		8.5kg	11.5kg